

# PORTAPATH

## access solutions for temporary access

**Portapath's** rugged anti-slip surface protects turf and prevents soil compaction. An excellent all weather, all year round surface, providing an innovative and reliable alternative to traditional flooring systems.



- Rugged anti-slip surface
- Provides Disabled and Wheelchair access
- Simple to change - just unclip and reconnect in minutes
- Unique drainage and ventilation slots prevent damage to grass
- Patented design of interlocking hinges - forms a stable floor with no dangerous seams

Easy to handle, simple to install. Portapath's unique design allows installation to be customised for each occasion, reducing time spent on site.

Suitable for Walkways, Turf Protection, Stadiums, Sports Arenas, Marquee Floors, Concerts, Catering Areas, Car Display Areas, Wheelchair Access, Exhibitions and Corporate Events.

## JAYLINE (Aust) Pty Ltd

ABN 40 080 838 393

Unit 1/16 Jusfrute Drive, West Gosford NSW 2250 Australia

Telephone: +61 2 4324 5266 Fax: +61 2 4325 0004

Email: [info@jaylineaust.com](mailto:info@jaylineaust.com) Website: [www.jaylineaust.com](http://www.jaylineaust.com)

# Portapath

## the solution for temporary access

The integral 'living hinge' unique to PORTAPATH, gives the system strength when locked together, while the innovative design also allows for quick disconnection. A simple separation unit is supplied for dismantling large areas.

PortaPath has enough air holes to allow the grass underneath to breathe. Water drains well, hence irrigating the grass while maintaining a safe and dry walking surface. From its design, PortaPath protects grass for several days.



The walking surface is an excellent all-weather, all year-round material providing an innovative and reliable alternative to traditional flooring systems.

It's durable,  
lightweight,  
attractive and  
affordable  
...it's  
PORTAPATH



### SPECIFICATIONS:

Dimensions: 31.11cm x 8.51cm x 1.59cm (LWH). Weight: 3.7 kg per m<sup>2</sup>

Load: Can support vehicles up to 2000kg.

Material: High impact UV protected polypropylene non-permeable 100% recyclable.

Cleaning: Can be swept or pressure washed. Standard cleaning fluids can be used.

Fire Rating: NFP92-501 Espiradateur Test M4.

Working Temperatures: 10°C to 40°C

Storage: Stored in rolls or flat sections.