

# J L A Temporary Access Solutions

A DIVISION OF

**Jayline (Aust) Pty Ltd**

Family of Products

1/16 Jusfrute Close,  
West Gosford, NSW, 2250, Australia  
Ph: +61 2 4324 5266 Fax: +61 2 4325 0004

Sales: [info@jaylineaust.com](mailto:info@jaylineaust.com)  
[www.jaylineaust.com](http://www.jaylineaust.com)

## YUKON RIG & ACCESS MAT 0011-YUKON-R SPECIFICATION SUMMARY

Width: 2.29 m  
Length: 4.27 m  
Thickness: 140 mm.  
Weight: 1360 kg

**Mat Composition...** The material is comprised from crumb rubber, urethane and fibre from recycled motor vehicle tyres.

**Absorption Characteristics...** Resist most liquids including water, petroleum products and insects.

**Temperature...** No adverse physical effects, although the stiffness will increase at extreme freezing temperatures. The mats can be removed during freezing conditions, as rubber will not bond to ice and snow.

**Abrasion Resistance...** Mat strength 2,000 PSI, Virtually indestructible, resist abrasive traffic over a long period.

**Rigidity...** Reinforced with a patented rigid spine.

**Insulation Value...** R-60 insulation rating.

**Installation...** Yukon mats are designed to be installed on solid to very soft to muddy surfaces.

**Traffic Type...** From foot pedestrian traffic to heavy industrial vehicles.

**Identification...** A unique identifier is embedded into each mat.

**Bevelled Edge...** All the Yukon Rigid mats have a bevelled edge to make it easy to pick them up and move into place.

**Lifting Lugs...** This is an optional feature installed into the mat. 4 per mat.

**Safety Features...** Anti-slip surface, low puncture hazard, resists fire, low tripping hazard, resists snow and ice build-up, low static electricity discharge.

**Handling Options...** Forklift, grapple equipped excavator, picker or crane.