

J L A Temporary Access Solutions

A DIVISION OF

Jayline (Aust) Pty Ltd

Family of Products

Unit 1, 8 Yandina Road
West Gosford, NSW, 2250, Australia
Ph: +61 2 4324 5266 Fax: +61 2 4325 0004

Sales: info@jaylineaust.com
www.jaylineaust.com

YUKON RIG & ACCESS MAT 0011-YUKON-R SPECIFICATION SUMMARY

Width: 2.29 m
Length: 4.27 m
Thickness: 140 mm.
Weight: 1360 kg

Mat Composition... The material is comprised from crumb rubber, urethane and fibre from recycled motor vehicle tyres.

Absorption Characteristics... Resist most liquids including water, petroleum products and insects.

Temperature... No adverse physical effects, although the stiffness will increase at extreme freezing temperatures. The mats can be removed during freezing conditions, as rubber will not bond to ice and snow.

Abrasion Resistance... Mat strength 2,000 PSI, Virtually indestructible, resist abrasive traffic over a long period.

Rigidity... Reinforced with a patented rigid spine.

Insulation Value... R-60 insulation rating.

Installation... Yukon mats are designed to be installed on solid to very soft to muddy surfaces.

Traffic Type... From foot pedestrian traffic to heavy industrial vehicles.

Identification... A unique identifier is embedded into each mat.

Bevelled Edge... All the Yukon Rigid mats have a bevelled edge to make it easy to pick them up and move into place.

Lifting Lugs... This is an optional feature installed into the mat. 4 per mat.

Safety Features... Anti-slip surface, low puncture hazard, resists fire, low tripping hazard, resists snow and ice build-up, low static electricity discharge.

Handling Options... Forklift, grapple equipped excavator, picker or crane.